

# LAMPE Standard Product Range

## Sewer sealing cushions with double cone

Area of operation			Article number			
Type	Ø from	Ø up to	Basic device for sealing	with special sealing	Bypass	with Bypass & special sealing
			Weight	Weight	Weight	Weight
1-150	80 mm (3 in)	150 mm (6 in)	76311 0,9 kg	76312 1 kg	76313 2,3 kg	76314 2,4 kg
1-400	100 mm (4 in)	400 mm (15 in)	76326 1,9 kg	76327 1,93 kg	76328 3,55 kg	76329 3,6 kg
1-600	200 mm (8 in)	600 mm (23 in)	76336 3,9 kg	76337 4,1 kg	76338 11,8 kg	76339 12 kg
1-800	300 mm (12 in)	800 mm (31 in)	76341 7,2 kg	76342 7,6 kg	76343 17,4 kg	76344 17,8 kg
1-1000	400 mm (15 in)	1.000 mm (40 in)	76346 11,8 kg	76347 12,4 kg	76348 23,7 kg	76349 24,3 kg
1-1400	500 mm (20 in)	1.400 mm (55 in)	76356 25,2kg	76357 27,9 kg	76358 41,5 kg	76349 44,2 kg
1-1500	500 mm (20 in)	1.500 mm (59 in)	76365 28,8 kg	76366 29,8 kg	76367 45,1 kg	76368 47,8 kg
1-1600	600 mm (23 in)	1.600 mm (63 in)	76361 38,5g	76362 41,8 kg	76363 56,7 kg	76364 58,5 kg
1-2200	1.000 mm (40 in)	2.200 mm (87 in)	76376 86 kg	76377 90,4 kg	76378 105 kg	76379 109,4 kg
1-2800	1.500 mm (59 in)	2.800 mm (110 in)	76391	76392	76393	76394

## Series 2000 with pipe bypass

Type	For use in pipe Ø from	For use in pipe Ø up to	Inner diameter of the cushion Weight without bypass pipe	Size of pipe-bypass (inner pipe)	Bypass pipe Outer diameter max.	Article number
40-80	400 mm (15 in)	800 mm (31 in)	285 mm (11 in) 8,7 kg	250 DN	250 mm (9,5 in)	76221
60-120	600 mm (23 in)	1.200 mm (47 in)	420 mm (16,5 in) 17,6 kg	400 DN	400 mm (15 in)	76222
80-170	800 mm (31 in)	1.700 mm (66 in)	650 mm (25,5 in) 27,7 kg	600 DN	630 mm (25 in)	76223
150-260	1.500 mm (59 in)	2.600 mm (102 in)	660 mm (26 in) 53 kg	600 DN	630 mm (25 in)	76224

**Attention:** For a correct and regulatory filling it is absolutely necessary, to use the original safety fittings \* (Standard: #71427), the original filling hose\*\* (Standard: 5m, #71523) as well as an adapter piece\*\*\* being suitable for the used air source!