

Combine the Welltech MidiMAX™ with a Welltech 340L/sec Portable Water Tower for a quick fill water supply system that increases productivity and reduces costs.

MidiMAX™

420,000 LITRES



Welltech MidiMAX™

- Generous 420,000 litre capacity or interconnectable to any capacity required;
- Transports on a single semi-trailer;
- Delivered, setup and commissioned, in less that a day;
- No ground disturbance, no excavation, no legacy issues;
- Engineered, cyclone rated, to withstand 288km/h winds - Region D, Importance Level 3;
- Restricted access from outside the tank meets all OHS regulations;
- Interconnect with one of our Portable Water Towers for high speed truck fill;
- Connect to a complete Welltech turnkey control system including; back to back base SCADA connectivity, autonomous pump control, leakage detection, SMS alarms and remote HMI;
- Robust, reliable, short to long term solution for continuous sustainable water storage/ supply;
- Designed and built in Western Australia by Welltech;
- Available with optional cover eliminating the risk of vermin or other contaminants making it suitable for potable water.

Welltech 340L/sec Portable Water Tower

- High volume 340L/sec flow rate;
- Large 60,000lt total capacity;
- Load a 15,000 litre water cart in just 45 seconds;
- Run multiple water carts from one installation with minimal waiting time.

Our fast, highly skilled teams are available to mobilise our in-house fleet at a moment's notice.

You can be assured we will deliver as promised and you will be supported by Welltech's guarantee of **Commitment = Satisfaction.**

An environmentally, sustainable superior solution

Built by



SHEET SIZE A1 REFERENCES	WELLTECH TOTAL WATER MANAGEMENT		WELLTECH MidiMAX™ WELLTECH 340 L/sec PWT		THIRD ANGLE PROJECTION
	REF No	DESCRIPTION	REV	DATE	
REVISIONS		DRAWN		APPROVED	
A		NH		DH	
30.08.2022		DH		DH	
DESCRIPTION		CKD		APP	
8		10		11	
9		10		11	
10		10		11	
11		10		11	
12		10		11	
13		10		11	
14		10		11	